

Materiallist

Marking of components	Material / product name	technical data / Dimension	Producer
		weight / strength	
Attchment loops	Nylon	7,2 g/m / Breaking load 110kg / 13mm spreads	Aqua Dynamiks
Accelerator lines	Nylon	Ø 4,0mm = Breaking load 350 daN	LIROS
Accelerator - brakeroll	B2 Pulley3, Rolle		B2-Engenierring, Sri Lanka
Accelerator lock	Brummelhook		B2-Engenierring, Sri Lanka
brake attachments	Nylon	7,2 g/m / Breaking load 110kg / 13mm spreads	Aqua Dynamiks
brake handhold	High Tanacity Poliester Yarn 20mm	25 g/m / 1000 kg Breaking load	Güth und Wolf, Germany
brake handhold attachment	High Tanacity Poliester Yarn 20mm	25 g/m / 1000 kg Breaking load	Güth und Wolf, Germany
brake handhold fixation	Magnet		B2-Engenierring, Sri Lanka
brake main line 2,3mm Ø	Dynema Lines DSL 300	2,3mm =250daN	LIROS
Lines: TSL 140/ 190/ 220 / 280 / TSL 380 und DSL 70,	Liros Lines		LIROS, Rosenberger Tauwerke
belt redirection	Stainless Steel	8g / Ø 3,8mm / Breaking load 800kg	B2-Engenierring, Sri Lanka
lines lock	Stainless Steel	12g / Ø 4,3mm / Breaking load 1000kg	B2-Engenierring, Sri Lanka
Top sail - A - B - C	Skytex 40 / Dokdo 30DMF	40 g/m ² / 40 g/m ² / (PA 6.6 HT)	NCV, France; Dominico Tex
V-Tape	Dokdo 30DMF	40 g/m ² (PA 6.6 HT)	Dominico Tex
Nose reinforcement	PPN Plastic		B2-Engenierring, Sri Lanka
Rips, Profile	Dokdo 30DFM	40 g/m ² (PA 6.6 HT)	Dominico Tex
Riser	Poliester / Aramid Yarn 20mm	31 g/m / 1900 kg Breaking load	Güth und Wolf, Germany
Undersail - A - B - C	Dokdo 30DMF	40 g/m ² (PA 6.6 HT)	Dominico Tex
Reinforcement pivot point B/C/D	D 170	170 g/m ²	Dominico Tex
sewing thread canopy	High Tanacity Poliester Yarn 150D/2	0,05 g/m ² / 2,9 kg Breaking load	Amann & Söhne GmbH, Germany
sewing thread lines	High Tanacity Poliester Yarn 150D/3	0,083 g/m ² / 3,2 kg Breaking load	Amann & Söhne GmbH, Germany